



Estate Dept./2022-23/16

April 19, 2022

**SUB: Quotation for Proposal for Structural strengthening work of R.C.C. Members in demonstration hall, common passage area, classroom and pantry area at 5th floor in Patkar Hall Bldg; S.N.D.T.W.U. Churchgate Campus.**

**Madam/Sir,**

Sealed Quotation are invited for Proposal for Structural strengthening work of R.C.C. Members in demonstration hall, common passage area, classroom and pantry area at 5th floor in Patkar Hall Bldg; S.N.D.T.W.U. Churchgate Campus. Interested authorized vendors are supposed to submit their quote along with their detail profile in the format given in "Annexure A" on their company letter head. Quotation should be submitted to the office of "The Registrar" at Churchgate campus on or before 26<sup>th</sup> April 2022 Contractor should submit their quotes in **two envelopes** enclosed in single envelope along with Technical bid envelope, financial bid envelope. Subject should be mentioned on each envelop.

Envelop may contains following documents in respective envelop:

**a) Technical Bid**

- i. Profile of the vendor
- ii. Work Experience Certificate ( not only the client list)
- iii. Registration Certificate
- iv. GST Certificate
- v. PAN Copy
- vi. If GST is not applicable then declaration of the same.
- vii. If any work which requires specific expertise/ technical specifications then the same should be mentioned.
- viii. Audited Financial Statements for last three years .(Income Tax)

**b) Financial Bid**

- i. Mentioning including all taxes
- ii. If required component wise then format to be given component wise
- iii. Terms and condition of contract.

Quotation should be submitted in closed envelop and on top write the subject. As mentioned in the notification

**The University reserves the right to reject any or all quotations without assigning any reasons thereof.**

Regards,

*Sharma*  
19/4/22  
(Dr. Vandana Sharma )  
Registrar (Addl.Charge)  
Registrar (Addl. Charge)  
SNDT Women's University  
Mumbai - 20.

6W  
V.S

**(Offer should filled on letter head)**

**Annexure A**

To,  
The Registrar  
SNDT Women's University,  
Churchgate, Mumbai

**Sub: Quotation for Structural strengthening work of R.C.C. Members in demonstration hall, common passage area, classroom and pantry area at 5th floor in Patkar Hall Bldg; S.N.D.T.W.U. Churchgate Campus.**

**Respected Madam/Sir,**

With reference to subject cited above we would like to furnish our quote with best rate possible as below:

<u>Sr. No.</u>	<u>Description of Item</u>	<u>Qty</u>	<u>Unit</u>	<u>Rate</u>	<u>Amount</u>
1	Removing Loose rust from the reinforcement bars by wire brushing. Light hammering etc. and applying sulphate and chloride free inorganic single component rust remover Rusticate as approved by Engineer in charge conforming to IS9077. The rusted surface shall become blackish non rusted color. After 24 hours of application of rust remover, loose particles shall be removed by brush. Apply one more coat of Rusticate. Apply bonding coat slurry of high performance acrylic polymer methyl 2- methylproenote copolymer with another emote as approved by Engineer in charge on entire surface. Mix 1 Kg of acrylic polymer with 0.5 kg of cement. Finish it with ready to use repair polymer modified mortar based on special cements, aldehyde based polymers with thixotropy modifying agents as approved by engineer in charge (The polymer Modified mortar (PMM) should attain min. Compressive strength of 20 N/mm <sup>2</sup> in 1 day and 30 N /mm <sup>2</sup> in 7 days )by adding 13-16% water by weight of polymer modified mortar for treatment to the damaged RCC members. Add 1 kg of Migrating Corrsion Inhibiting Admixture as approved by Engineer in charge per 25 kg bag of polymer modified Mortor,it can be trowl applied or sprayed. When applying by hand, polymer modified mortar must be forced tightly into the substrate to ensure complete contact with the substrate. (if scaffolding is required, same shall be provided and will be paid under	50.00	Sqm.		

	relevant item)(Upto 15 mm thick time)				
2	Providing and applying gypsum plaster ( with Gypsum material of Gypsum India / Mega Sign or equivalent make ) with finishing with gypsum material in 10 to 13 millimeter thickness to previously plastered surface / or on newly brick surface ( Excluding rough cast plaster ) in all position including preparing and Finishing the surface scaffolding etc.complete.	50.00	Sqm.		
3	Breaking/ Chipping carefully the loose concrete plaster of distressed member without damaging existing strong concrete by menas of sharp chissle which should tempered regularly or high frequency low impact hammers used, cleaning the surface by water jet pressure pump	50.00	Sqm.		
4	Lowering down the debris obtained from breaking and removing the cement plaster/burnt brick masonry of the first floor by any means without causing dust nuisance and damage to strcture, stacking the same as and where directed including cleaning the site complete.	4.50	Cum		
5	Removing any kind of debris including loading in truck and conveying to dumping point approved by MCGM, unloading , spreading etc. complete. With all leads and lifts.	4.50	Cum		
	Net Total				
	Add GST as Applicable				
	<b>Total</b>				

All the terms and conditions given in notifications are studied thoroughly and accepted fully.

Thanking You,

Yours Faithfully,

Name of Company

Signature of the Proprietor

Date:

Note: Enclose GST number, PAN number, declaration if GST is not applicable